


Curva 90° Short Radius Seamless

Norme: ASME B16.9 – ASTM A403 WP-S

Materiale: Aisi 304L EN 1.4307 – Aisi 316L EN 1.4404

cod. 308



| De x Spessore mm | Dimensioni | R mm | Stock | Peso kg |
|------------------|----------------|------|-------|---------|
| 33,40 x 2,77 | 1" SCH 10S | 25 | R | 0,10 |
| 33,40 x 3,38 | 1" SCH 40S | 25 | D | 0,12 |
| 33,40 x 4,55 | 1" SCH 80S | 25 | R | 0,13 |
| 42,16 x 2,77 | 1.1/4" SCH 10S | 32 | R | 0,15 |
| 42,16 x 3,56 | 1.1/4" SCH 40S | 32 | D | 0,20 |
| 42,16 x 4,85 | 1.1/4" SCH 80S | 32 | R | 0,22 |
| 48,26 x 2,77 | 1.1/2" SCH 10S | 38 | R | 0,22 |
| 48,26 x 3,68 | 1.1/2" SCH 40S | 38 | D | 0,29 |
| 48,26 x 5,08 | 1.1/2" SCH 80S | 38 | R | 0,32 |
| 60,33 x 2,77 | 2" SCH 10S | 51 | R | 0,37 |
| 60,33 x 3,91 | 2" SCH 40S | 51 | D | 0,51 |
| 60,33 x 5,54 | 2" SCH 80S | 51 | R | 0,60 |
| 73,03 x 3,05 | 2.1/2" SCH 10S | 64 | R | 0,62 |
| 73,03 x 5,16 | 2.1/2" SCH 40S | 64 | D | 1,02 |
| 73,03 x 7,01 | 2.1/2" SCH 80S | 64 | R | 1,14 |
| 88,90 x 3,05 | 3" SCH 10S | 76 | R | 0,90 |
| 88,90 x 5,49 | 3" SCH 40S | 76 | D | 1,50 |
| 88,90 x 7,62 | 3" SCH 80S | 76 | R | 1,85 |
| 114,30 x 3,05 | 4" SCH 10S | 102 | R | 1,72 |
| 114,30 x 6,02 | 4" SCH 40S | 102 | D | 3,12 |
| 114,30 x 8,56 | 4" SCH 80S | 102 | R | 3,05 |
| 141,30 x 3,40 | 5" SCH 10S | 127 | R | 2,75 |
| 141,30 x 6,55 | 5" SCH 40S | 127 | R | 5,28 |
| 168,28 x 3,40 | 6" SCH 10S | 152 | D | 4,15 |
| 168,28 x 7,11 | 6" SCH 40S | 152 | R | 7,15 |
| 168,28 x 10,97 | 6" SCH 80S | 152 | R | 11,79 |
| 219,08 x 3,76 | 8" SCH 10S | 203 | R | 8,00 |
| 219,08 x 8,18 | 8" SCH 40S | 203 | R | 17,05 |