


Curva 90° Short Radius Welded

Norme: ASME B16.9 – ASTM A403 WP-W

Materiale: Aisi 304L EN 1.4307 – Aisi 316L EN 1.4404

cod. 308W



De x Spessore mm	Dimensioni	R mm	Stock	Peso kg
88,90 x 3,05	3" SCH 10S	76	R	0,90
88,90 x 5,49	3" SCH 40S	76	D	1,50
114,30 x 3,05	4" SCH 10S	102	R	1,72
114,30 x 6,02	4" SCH 40S	102	D	3,12
141,30 x 3,40	5" SCH 10S	127	R	2,75
141,30 x 6,55	5" SCH 40S	127	R	5,28
168,28 x 3,40	6" SCH 10S	152	D	4,15
168,28 x 7,11	6" SCH 40S	152	R	7,15
219,08 x 3,76	8" SCH 10S	203	R	8,00
219,08 x 8,18	8" SCH 40S	203	R	17,05
273,05 x 4,19	10" SCH 10S	254	R	12,40
273,05 x 9,27	10" SCH 40S	254	R	24,00
323,85 x 4,57	12" SCH 10S	305	R	17,20
323,85 x 9,53	12" SCH 40S	305	R	38,10
355,60 x 4,78	14" SCH 10S	406	R	23,09
355,60 x 9,52	14" SCH 40S	406	R	45,40
406,40 x 4,78	16" SCH 10S	457	R	30,84