


Riduzione M/F microfusa - Fig. 241

Norme: ISO 7/1 GAS Conico X ISO 228/1 GAS Cilindrico

Materiale: Aisi 316 EN 1.4401

cod. 447



DN1	DN1 inch	DN2	DN2 inch	CH mm	H mm	Stock
8	1/4"	5	1/8"	17	17	D
10	3/8"	5	1/8"	21	18	D
		8	1/4"	21	18	D
15	1/2"	8	1/4"	26	20,5	D
		10	3/8"	26	20,5	D
20	3/4"	8	1/4"	30,5	23,5	D
		10	3/8"	30,5	23,5	D
		15	1/2"	30,5	23,5	D
25	1"	15	1/2"	37,5	26,5	D
		20	3/4"	37,5	26,5	D
32	1 1/4"	15	1/2"	45,5	29	D
		20	3/4"	45,5	29	D
		25	1"	45,5	29	D
40	1 1/2"	15	1/2"	52	31	D
		20	3/4"	52	31	D
		25	1"	52	31	D
		32	1 1/4"	52	31	D
50	2"	25	1"	62	36	D
		32	1 1/4"	62	36	D
		40	1 1/2"	62	36	D
65	2 1/2"	25	1"	79,5	39	D
		32	1 1/4"	79,5	39	D
		40	1 1/2"	79,5	39	D
		50	2"	79,5	39	D
80	3"	50	2"	92	43,5	D
		65	2 1/2"	92	43,5	D